

# AES CABINET HYBRID INVERTER INTEGRATION

## Compatible with SOLIS 29.9 to 50K Inverters

### High-Voltage Energy Storage Made Easy for Commercial and Industrial Applications.

Discover's AES CAB-106, CAB-160, and AES 210HV battery cabinets pair seamlessly with the Solis S6-EH3P(29.9-50)K-H-AU hybrid-inverter series, offering a simple, scalable, and proven energy storage solution for commercial and industrial applications. Whether you're reducing demand charges, maximising solar self-consumption, or adding reliable backup, this system is ready.

#### Plug-and-Play Integration

**Voltage Match.** The nominal voltages of the CAB-106 (332 VDC), CAB-160 (499 VDC), and AES 210HV (665 VDC) align with Solis's 150–800 VDC battery range.

**Dual Battery Terminals.** Connect directly to both Solis battery ports using the cabinet's internal fused DC distribution.

**Managed (closed-loop) control.** Built-in LYNK II Gateway enables real-time CANBus communication with Solis BMS1/BMS2.

**Black-start capable.** Black-start capable, with event logging, SoC reporting, and full inverter coordination.



Multi-unit Residential  
Buildings



EV Charging  
Stations



Supermarkets &  
Retails Shops



Banks, Hospitals  
& Schools



Industrial  
Sites

## BUILT FOR EASY INTEGRATION AND FLEXIBLE GROWTH

Solis Inverters	CAB-106	Rated Output	Usable Energy	Estimated Autonomy
1 x 29.9K (400 V)	1 x CAB-106	29.9 kW	104 kWh	~3.5 hours
1 x 30K (400 V)	1 x CAB-106	30 kW	104 kWh	~3.5 hours
1 x 40K (400 V)	1 x CAB-106	40 kW	104 kWh	~2.5 hours
1x 50K (400 V)	1 x CAB-106	50 kW	104 kWh	~2 hours
1x 50K (400 V)	2 x CAB-106	50 kW	208 kWh	~4.1 hours
2x 50K (400 V)	1 x CAB-106	100 kW	104 kWh	~1 hour

*Note: Each CAB-106 operates independently – no DC bus paralleling. Inverters are paralleled on the AC bus as specified in the Solis AU installation guide.*

Solis Inverters	CAB-160	Rated Output	Usable Energy	Estimated Autonomy
1 x 29.9K (400 V)	1 x CAB-160	29.9 kW	157 kWh	~5¼ hours
1 x 30K (400 V)	1 x CAB-160	30 kW	157 kWh	~5¼ hours
1 x 40K (400 V)	1 x CAB-160	40 kW	157 kWh	~3.9 hours
1x 50K (400 V)	1 x CAB-160	50 kW	157 kWh	~3 hours
1x 50K (400 V)	2 x CAB-160	50 kW	314 kWh	~6¼ hours
2x 50K (400 V)	1 x CAB-160	100 kW	157 kWh	~3½ hours

*Note: Each CAB-160 operates independently – no DC bus paralleling. Inverters are paralleled on the AC bus as specified in the Solis AU installation guide.*

Solis Inverters	AES 210HV	Rated Output	Usable Energy	Estimated Autonomy
1 x 29.9K (400 V)	1 x AES 210HV	29.9 kW	209 kWh	~7 hours
1 x 30K (400 V)	1 x AES 210HV	30 kW	209 kWh	~7 hours
1 x 40K (400 V)	1 x AES 210HV	40 kW	209 kWh	~5 hours
1x 50K (400 V)	1 x AES 210HV	50 kW	209 kWh	~4 hours
1x 50K (400 V)	2 x AES 210HV	50 kW	418 kWh	~8 hours
2x 50K (400 V)	1 x AES 210HV	100 kW	209 kWh	~2 hours

*Note: Each AES 210HV cabinet operates independently – no DC bus paralleling. Inverters are paralleled on the AC bus as specified in the Solis AU installation guide.*

**Scalable.** From 200 kWh to 4 MWh of usable energy.

**Pre-assembled and factory tested.** Reduced installation time and on-site labour costs.

**Compatible.** With all models (29.9K to 50K) of Solis HV Hybrid Inverters.

**Efficient.** Liquid Cooled and temperature managed battery cells.

**Year-round operation.** All climate operation. Outdoor-rated (IP55 equivalent to NEMA 3R)

**Optimised.** Multi-tiered Battery Management System.

**Managed.** 24/7 Monitoring and Alerts.

**Certified.** UL1973, UL9540A, UL9540 DC ESS, CEC listing pending.

**Safe.** Heat and Smoke Detection, Ventilation, Dehumidifier, Fire Suppression, Flood Sensor.

**Remote Monitoring and Control.** Real-time monitoring via LYNK Cloud or local diagnostics using LYNK Access PC software.

LEARN MORE ABOUT THE AES 210HV AND OTHER C&I SOLUTIONS.

